

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 January 2004 (08.01.2004)


PCT

(10) International Publication Number
WO 2004/002756 A1

- (51) International Patent Classification?: **B60C 15/05**, 15/06, 15/00
- (74) Agents: **BOTTERO, Carlo et al.**; Pirelli S.p.A, Viale Sarca, 222, I-20126 Milano (IT).
- (21) International Application Number:
PCT/IB2002/002457
- (22) International Filing Date: 27 June 2002 (27.06.2002)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): **PIRELLI PNEUMATICI S.P.A.** [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **LACAGNINA, Claudio** [IT/IT]; Via Dell'acqua, 18/2, I-21052 Busto Arsizio, (IT). **NOTO, Rodolfo** [IT/IT]; Via Pertini, 9, I-20064 Gorgonzola (IT).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TYRE FOR VEHICLE WHEELS WITH REINFORCED BEAD STRUCTURE



(57) **Abstract:** Tyre for vehicle wheels, comprising a toroidal carcass that has a central crown portion and two axially opposite sidewalls ending in a pair of beads for anchoring the tyre (1) to a corresponding mounting rim, each bead comprising at least an annular reinforcing core (5, 6), a tread band (9) positioned at the crown and coaxially extended about said carcass, provided with a relief pattern for the rolling contact with the road, and a belt structure (8) coaxially interposed between said carcass and said tread band (9), said carcass comprising at least a carcass ply (7), said at least one carcass ply (7) having its own ends anchored to said annular reinforcing cores, wherein said at least one carcass ply (7) comprises a portion that encloses within it at least an insert (15) in proximity to said annular reinforcing cores (5, 6).